Produkte
Mainboard Serie
»X79 Extreme6/GB
»Überblick
»Spezifikationen
»Download
»Handbuch
»FAQ
»CPU Support Liste
»Speicher Support Liste
»Beta-Zone

X79 Extreme6/GB

Translate

- Premium Gold Caps (2.5 x longer life time), 100% Japan-made high-quality Conductive Polymer Capacitors
- Intel® Core™ i7 processor family for the LGA 2011 Socket
- Supports Quad Channel DDR3 2400+(OC), 8 DIMM slots, Max. capacity up to 64GB
- Digi Power Design, 12 + 2 Power Phase Design
- 3 x PCIe 3.0 x16 Slots, Supports AMD 3-Way CrossFireX™ and NVIDIA® 3-Way SLI™
- Broadcom Dual LAN with Teaming Function
- Supports ASRock X-FAN, XFast RAM, XFast LAN, XFast USB, Graphical UEFI, UEFI System Browser, AXTU
- Creative Sound Core3D 7.1 CH, Supports THX TruStudio PRO™
- Free Bundle : ASRock Game Blaster, 1 x Front USB 3.0 Panel, CyberLink MediaEspresso 6.5 Trial, ASRock MAGIX Multimedia Suit

Dieses Modell wird nicht in allen Regionen der Welt verkauft. Bezüglich der Verfügbarkeit in Ihrer Region kontaktieren Sie bitte Ihren Händler.

Youtube Live Demo

ASRock XFast RAM Technology

Auszeichnungen

3/7/2012 **Hothardware.com** - Recommended
Das ASRock X79 Extreme6/GB performte wirklich sehr gut. Der Game Blaster ist eine äußerst attraktive Komponente für Gamer. Das ASRock X79 Extreme6/GB wurde mit dem "Recommended Award" von Hothardware.com ausgezeichnet.

Produkt Spezifikationen

Generelles	
CPU	- Supports Intel® Core™ i7 processor family for the LGA 2011 Socket - Digi Power Design - 12 + 2 Power Phase Design - Supports Intel® Turbo Boost 2.0 Technology - Supports Hyper-Threading Technology - Supports Untied Overclocking Technology
Chipsatz	- Intel® X79
Arbeitsspeicher	- Quad Channel DDR3 memory technology - 8 x DDR3 DIMM slots - Supports DDR3 2400+(OC)/2133(OC)/1866(OC)/1600/1333/1066 non-ECC, un-buffered memory - Supports DDR3 ECC, un-buffered memory with Intel® Workstation 1S Xeon processors E5 16xx/26xx/46xx series in socket LGA 2011 - Max. capacity of system memory: 64GB* - Supports Intel® Extreme Memory Profile (XMP) 1.3 / 1.2 *Due to the operating system limitation, the actual memory size may be less than 4GB for the reservation for system usage under Windows® 32-bit OS. For Windows® 64-bit OS with 64-bit CPU, there is no such limitation.
BIOS	- 64Mb AMI UEFI Legal BIOS with GUI support - Supports "Plug and Play" - ACPI 1.1 Compliance Wake Up Events - Supports jumperfree - SMBIOS 2.3.1 Support - CPU, VCCSA, DRAM, VTT, CPU PLL, PCH1.1V, PCH1.5V Voltage Multi-adjustment
Audio, Video und Netzwerk	
Grafik	- n/a
Audio	ASRock Game Blaster Audio - Supported by the bundled ASRock Game Blaster - Creative Sound Core3D quad-core sound and voice processor - Supports THX TruStudio™ PRO - Supports CrystalVoice - Supports EAX1.0 to EAX5.0Onboard Audio - 7.1 CH HD Audio with Content Protection (Realtek ALC898 Audio Codec) - Premium Blu-ray audio support - Supports THX TruStudio™

LAN	- PCIE x1 Gigabit LAN 10/100/1000 Mb/s - Broadcom BCM57781 - Supports Wake-On-LAN - Supports Energy Efficient Ethernet 802.3az - Supports Dual LAN with Teaming function with the bundled ASRock Game Blaster - Supports PXE
Erweiterungsslots/Konnektivität	
Steckplätze	- 3 x PCI Express 3.0 x16 slots (PCIE1 @ x16 mode; PCIE3 @ x16 mode; PCIE4 @ x8 mode) - 1 x PCI Express 2.0 x1 slot - 2 x PCI slots - Supports AMD Quad CrossFireX™ , 3-Way CrossFireX™ and CrossFireX™ - Supports NVIDIA® Quad SLI™ , 3-Way SLI™ and SLI™
SATA3	- 2 x SATA3 6.0 Gb/s connectors by Intel® X79, support RAID (RAID 0, RAID 1, RAID 5, RAID 10 and Intel® Rapid Storage 3.0), NCQ, AHCI and "Hot Plug" functions - 3 x SATA3 6.0 Gb/s connectors by ASMedia ASM1061, support NCQ, AHCI and "Hot Plug" functions
USB 3.0	- 4 x Rear USB 3.0 ports by TI, support USB 1.0/2.0/3.0 up to 5Gb/s - 1 x Front USB 3.0 header (supports 2 USB 3.0 ports) by ASMedia ASM1042, supports USB 1.0/2.0/3.0 up to 5Gb/s
Anschluss	- 4 x SATA2 3.0 Gb/s connectors, support RAID (RAID 0, RAID 1, RAID 5, RAID 10 and Intel® Rapid Storage 3.0), NCQ, AHCI and Hot Plug functions - 5 x SATA3 6.0 Gb/s connectors - 1 x IR header - 1 x CIR header - 1 x COM port header - 1 x HDMI_SPDIF header - 1 x IEEE 1394 header - 1 x Power LED header - CPU/Chassis/Power/SB FAN connector - 24 pin ATX power connector - 8 pin 12V power connector - SLI/XFire power connector - 3 x USB 2.0 headers (support 6 USB 2.0 ports) - 1 x USB 3.0 header (supports 2 USB 3.0 ports) - 1 x Dr. Debug with LED
ATX-Blende	I/O Panel - 1 x PS/2 Mouse Port - 1 x PS/2 Keyboard Port - 1 x Coaxial SPDIF Out Port - 1 x Optical SPDIF Out Port - 4 x Ready-to-Use USB 2.0 Ports - 1 x eSATA3 Connector - 4 x Ready-to-Use USB 3.0 Ports - 1 x RJ-45 LAN Port with LED (ACT/LINK LED and SPEED LED) - 1 x IEEE 1394 Port - 1 x Clear CMOS Switch with LED - HD Audio Jack: Side Speaker / Rear Speaker / Central / Bass / Line in / Front Speaker / Microphone
Sonstige Features/Verschiedenes	
Einzigartige Features	- ASRock Extreme Tuning Utility (AXTU) - ASRock Instant Boot - ASRock Instant Flash - ASRock APP Charger - ASRock SmartView - ASRock XFast USB - ASRock XFast LAN - ASRock XFast RAM - ASRock X-FAN - ASRock Crashless BIOS - Hybrid Booster: - CPU Frequency Stepless Control - ASRock U-COP - Boot Failure Guard (B.F.G.) - Good Night LED
Smart Switch	- 1 x Power Switch with LED - 1 x Reset Switch with LED - 1 x Clear CMOS Switch with LED
Support-CD	- Drivers, Utilities, AntiVirus Software (Trial Version), CyberLink MediaEspresso 6.5 Trial, ASRock Software Suite (ASRock MAGIX Multimedia Suite - OEM)
Produktzubehör	- 1 x ASRock SLI_Bridge_2S Card - 1 x ASRock 3-Way SLI-2S1S Bridge Card - 1 x ASRock Game Blaster - Quick Installation Guide, Support CD, I/O Shield - 5 x SATA Data Cables (optional) - 1 x Front USB 3.0 Panel - 4 x HDD Screws - 6 x Chassis Screws - 1 x Rear USB 3.0 Bracket
Hardware überwachung	- CPU Temperature Sensing - Chassis Temperature Sensing - CPU/Chassis/Power/SB Fan Tachometer - CPU/Chassis Quiet Fan (Allow Chassis Fan Speed Auto-Adjust by CPU Temperature) - CPU/Chassis/SB Fan Multi-Speed Control - Voltage Monitoring: +12V, +5V, +3.3V, CPU Vcore
Formfaktor	- ATX Form Factor: 12.0-in x 9.6-in, 30.5 cm x 24.4 cm - Premium Gold Capacitor design (100% Japan-made high-quality Conductive Polymer Capacitors)
Betriebssystem	- Microsoft® Windows® 7 / 7 64-bit / Vista™ / Vista™ 64-bit / XP / XP 64-bit compliant
Zertifizierungen	- FCC, CE, WHQL - ErP/EuP Ready (ErP/EuP ready power supply is required)

Achtung:
Bitte beachten Sie, dass Overclocking, inklusive dem Verändern von BIOS-Einstellungen und der Nutzung von Overclockingprogrammen von Drittherstellern, immer ein gewisses Risiko bürgt. Overclocking kann ihre Systemstabilität beeinflussen oder aber zu Schäden Ihrer Komponenten und Geräte führen. Die Ausführung geschieht auf eigene Gefahr und Kosten. Für Schäden die durch Overclocking verursachet werden sind wir nicht verantwortlich.

Die Spezifikationen können ohne vorherigen Hinweis geändert werden. Die Marken und Produktnamen sind Schutzmarken der jeweiligen Firmen. Alle Konfigurationen die von den original Spezifikationen abweichen werden nicht garantiert.

© 2002-2012 ASRock Inc Alle Rechte vorbehalten | Informationen die auf asrock.com veröffentlicht werden, können ohne Hinweis geändert werden.
Das oben abgebildete User-Interface ist ein Referenzbeispiel. Das tatsächliche User-Interface kann von der Abbildung abweichen.